

Osprey Product Comparison Chart

		100	210	230	240e	EASE	440	450e	530	700e HD
Video Inputs	Composite (RCA)	3								
	Composite (BNC)		•	•	•	•	4	4	•	
	S-Video (Mini-DIN)	•	•	•		•			•	
	Y/C (BNC)				•					
	Analog Component Y/Pb/Pr (BNC)				•					
	DV (IEEE 1394a, 1934b)					•				
	SDI (BNC)								•	•
	HD-SDI (BNC)									•
Audio Inputs	Unbalanced Stereo (RCA)		•	•	•	•	4	4	•	
	Balanced Stereo (RCA)			•	•	•	•	•	•	
	DV (IEE 1394a, 1394b)					•				
	AES/EBU (XLR)								•	
	Embedded SDI								•	•
A/V Loop-Out	Composite (BNC)								•	
	S-Video (mini-DIN)								•	
	Unbalanced Stereo (3.5mm)		•	•	•	•				
	Unbalanced Stereo (RCA)								•	
A/V Output	DV (IEEE 1394a, 1394b)					•				
Physical	Bus Interface	PCI	PCI	PCI/PCI-X	PCIe	PCI/PCI-X	PCI/PCI-X	PCIe	PCI/PCI-X	PCIe
	Dimensions	Low Profile	Full Height	Low Profile	Low Profile	Full Height	Full Height	Full Height	Full Height	Low Profile
OS Support	Windows XP/XP Pro	•	•	•	•	•	•	•	•	•
	Windows Server 2003	•	•	•	Q4 2008	•	•	Q4 2008	•	Q4 2008
	Linux (open source)	•	•	•			•		•	
Compliance	RoHS	•	•	•	•	•	•	•	•	•
	CE Mark	•	•	•	•	•	•	•	•	•
	FCC 47CFR Part 15 Class A					•	•	•	•	
	FCC 47CFR Part 15 Class B		•	•	•					•

For more information on ViewCast products, visit www.viewcast.com.